



GRANDSTREAM

---

CONNECTING THE WORLD

# AGENDA

1

INTRODUCTION GRANDSTREAM

2

NEW – DP720/750 IP CORDLESS DECT  
HT800 ANALOG ADAPTER SERIES

3

ROADMAP - UPCOMING PRODUCTS



# Company Overview

Founded in Boston, MA USA in 2002

500+ employees with offices/presence in 10 countries

Leading manufacturer of IP Voice/Video Telephony and Surveillance solutions

Primarily serving small-to-medium size businesses (SMBs) and consumer markets



Boston  
Los Angeles  
Dallas



Casablanca  
Morocco



Malaysia



Spain



Colombia



Shenzhen  
Hangzhou  
China



Valencia  
Venezuela



Lebanon



Ukraine



Israel

3 Global Warehouses



Shenzhen  
China



Los Angeles



Netherlands



## VoIP Product Lines

IP Multimedia Phones

Enterprise IP Phones

Small Business / Home Office IP Phones

Analog Gateways & ATAs

IP PBX Appliances

Video & Audio Conference Systems



## Surveillance Product Lines

IP Video Encoder/Decoder

Outdoor IP Cameras


Video Management Software

Network Video Recorder



# Full Unified Communication Solution

CEO's office



# Product Interoperability

## IP-PBX and Softswitch




## ITSPs



# GAPS

(Grandstream Automatic Provisioning System)

Partners need to access the GAPS web portal before connecting devices to the network. Then, *partners can easily redirect devices to their own provisioning server or their customers.*



Only available via our CertifiedPartner

# NEW PRODUCT SERIES

---

DECT DP7xx Series  
HT800 Analog Adaptors



**NEW**

# DP750

## Long-range DECT VoIP Base Station

- Pairs with up to 5 DP720 DECT handsets
- 3-way voice conferencing, full HD audio
- Supports 300m range outdoors, 50m indoors
- Supports up to 10 SIP accounts and 4 concurrent calls
- Built-in PoE
- Up to 20-hour talk time, 250-hour standby time
- Use with Grandstream's UCM for Zero Config Provisioning
- DP750 – Base, DP720 – Handset





**NEW**

# DP720

## DECT Cordless HD Handset

- Up to 20-hour talk time, 250-hour standby time
- 1.8 inch TFT LCD color screen
- Integrated 3.5mm headset jack, speakerphone
- Multi-line access for up to 10 lines per handset
- Up to 5 DP720 handsets per DP750 base station

	DP715 Base Station	DP750 Base Station
		
Handsets	5	5
SIP Accounts	5	10
Concurrent Calls	4	4
Hunting Group Modes	Linear mode, Parallel mode, Shared Line mode	Circular mode, Linear mode, Parallel mode, Shared Line mode
Voice Codecs	G.711μ/a-law, VAD, CNG, PLC, G.723.1, G.729A/B, G.726-32, iLBC	G.711μ/a-law, VAD, CNG, PLC, AJB, G.723.1, G.729A/B, G.726-32, iLBC, G.722, OPUS, G.722.2/AMR-WB (special order)
Phonebook	200 entries per handset	3000 entries (downloadable phonebook XML)
Call logs	10 dialed call records, 20 received call records per handset	300 records
LDAP Support	No	Yes
Security	SIP/TLS, SRTP, HTTPS, AES-256	SIP/TLS, SRTP, HTTPS, AES-256, 802.1x
Upgrade/Provisioning	HTTP, HTTPS, TFTP, TR-069, XML	HTTP, HTTPS, TFTP, TR-069, XML
Languages	English only	Arabic, Chinese (Simplified, Traditional), Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovenian, Spanish, Swedish, Turkish
LED indicators	4 LED indicators: Power, Network, Register, Call	5 LED indicators: Power, Network, Register, Call, DECT
Range	300 meters outdoors and 50 meters indoors	300 meters outdoors and 50 meters indoors
PoE Support	No	Yes (IEEE802.3af Class 1)
Dimensions (H x W x D)	75 x 105 x 85 mm	28.5 x 130 x 90 mm
Weight	95g	143g
Universal Power Supply	Output: 6VDC, 500mA	Output: 5VDC, 1A Micro-USB connection

	DP710 Handset	DP720 Handset
		
<b>LCD</b>	1.7 inch (102x80) LCD with blue backlight	1.8 inch (128x160) color TFT LCD
<b>Headset</b>	No	Yes (3.5mm headset jack)
<b>MWI LED</b>	No (VMWI available on DP715 base station only)	3-Color MWI LED
<b>Keypad buttons</b>	20	23
<b>Hearing Aid Compatibility</b>	No	Yes
<b>HD Audio</b>	No	Yes, both on Handset and Speakerphone
<b>Multi-line Access</b>	No (can only use one SIP account for outgoing calls)	Yes (can use up to 10 sip accounts as lines for outgoing calls)
<b>Languages</b>	English, German, Italian, French, Spanish, Portuguese, Dutch, Czech, Danish, Greek, Norwegian, Russian, Polish, Swedish, Turkish	Arabic, Chinese (Simplified, Traditional), Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovenian, Spanish, Swedish, Turkish
<b>Battery Life</b>	10-hour talk time 80-hour standby time 16-hour charging time	25-hour talk time 200-hour standby time 12-hour charging time
<b>Charging method</b>	On the cradle	On the cradle or via micro-USB port (for alternative charging or non-battery operation)
<b>Dimensions (H x W x D)</b>	Handset: 160 x 46 x 22 mm Cradle: 53 x 75 x 60 mm	Handset: 155 x 50 x 26 mm Cradle: 35 x 63.5 x 54 mm
<b>Weight</b>	Handset:104g Cradle: 102g	Handset: 138g Cradle: 71g
<b>Universal Power Supply</b>	Output: 7VDC, 420mA	Output: 5VDC, 1A Micro-USB connection

## Multiple SIP Accounts

Up to 10 distinct SIP accounts per system

- Each handset may map to any SIP account(s)
- Each SIP account may map to any handset(s)



**SIP**



## Enhanced Telephony Features

Easy access to common telephony features,  
directly from the phone menu

- Hold
- Transfer/Forward
- 3-way conference

**Other features include:**

- Downloadable phone book
- Call waiting
- Auto Answer
- Click-to-dial
- Flexible dial plan
- Music on hold





## Accessibility

- Integrated 3.5mm headset jack
- Speakerphone for hands free mode
- Belt clip for easy mobility
- Micro-USB port for alternative charging and non-battery operation
- Hearing Aid Compatibility (HAC) compliant



COMING SOON!

# HT800 Series

## Analog Adaptors

- Same chip platform, almost same firmware

### HT801/802:

- 1/2-FXS, 1x LAN, faster processor and 2x more memory than HT701/702
- Same price as HT701/702 respectively

### HT812:

- 2x FXS, 2x memory,
- Gigabit WAN+LAN with faster routing performance than HT502 - TR-069



# UPCOMING PRODUCT SERIES

---

GWN Series Networking Solutions



COMING SOON!



# GWN Series

## New Product line Introduction

- Seamlessly connect the GWN router with multiple Access Points to provide wired and wireless network access for a large area
- A single management interface that allows for easy configuration for this collection of devices



# GWN7000



# GWN7000

## Feature Overview

- Controller-less Architecture (APs)
- Unified Management
- VPN Routing
- Multiple Network Support
  - ✓ Run private/employee and customer networks off the same device
- Customer Access
  - ✓ Monetize customer access- pending
  - ✓ Easily manage customer network resource usage



 COMING SOON!

# GWN7000

## Gigabit Multi-WAN VPN Router

- 7x Gigabit ports (2x WAN + 4x LAN + 1x NET)
  - ✓ NET port configurable as LAN (default), WAN or VoIP/SIP QOS port (Q4/2016 SW release)
- Integrated PoE+
- 2x USB 3.0 ports (for printer/storage/3G or 4G LTE dongle/etc)
- 10Gbps aggregate switching performance
- 1 million packet/second routing performance
- 200Mbps (soft crypto)—300+Mbps (hardware crypto) VPN performance
- Central management capability with Full Provisioning Agent for large network (>100++ APs) – pending “Cloud Management System)



## Multiple Network Support

- One GWN7000 can support up to 16 zones
- Each zone is a separate network
- The zone comprises both wired and wireless clients
- Automatically tag/untag VLAN for wireless clients
- LAN ports may be segregated to support distinct wired networks with a single GWN7000




# GWN7000

## Unified Management Highlights

- No extra app required (Some competitors requires PC with Java app)
- No fees for small/medium sized network
- Entire network at a glance
  - User statistics and management
  - Aggregate usage



# Unified Management Interface



COMING SOON!

# GWN7610 Indoor Wi-Fi AP





# GWN7610

## Indoor Wi-Fi AP



- Up to 250 client devices
- Supports a/b/g/n Wi-Fi Standards
- **2.4GHz Frequency**
  - 450Mbps wireless throughput with 3x3:3 MIMO
- **5GHz Frequency**
  - 1300Mbps wireless throughput with 3x3:3 MIMO for
- 2x Gigabit network ports with integrated PoE/PoE+
- Kensington lock – Daisy Chain capabilities
- Max range of 150 meters



# UPCOMING PRODUCT SERIES

---

GXP1700 Series  
GDS3710 IP Video Door Solution



COMING SOON!

# GXP1700 Series

## SMB Multi-line Key & Digital BLF

Spec	GXP1780	GXP1782	GXP1760
Line Keys/ BLF Keys	4+4	4+4	3+3
LCD	200x80	200x80	200x80
Network Ports	2x 100M ports	2x Gigabit ports	2x 100M ports
PoE	Yes	Yes	Yes
Power Supply	Included	Included	Included



COMING SOON!

# GDS3710

## IP Video Door Solution



- High-definition IP surveillance camera – ideal for monitoring from wall to wall without blind spots
- Powered by an advanced Image Sensor Processor (ISP) and state of the art image algorithms, it delivers exceptional performance in all lighting conditions.
- SIP/VoIP for 2-way audio and video streaming to smart phones and SIP phones
- Integrated PoE, LEDs, HD loudspeaker, RFID, motion detector, lighting control switch
- Together with Grandstream videophone, mobile Apps, and Network Video Recorder (NVR), the GDS3710 provides a powerful recording and monitoring solution



# ANY QUESTIONS?

---

THANK YOU!

